

SYSTEM AND METHOD FOR BOOKMARKING A ROUTE

5 FIELD OF THE INVENTION

The present invention relates generally to communication systems. In particular, the present invention provides a method and system for storing a relationship between two or more points (such as a route between the two points) and obtaining information about that relationship.

10

BACKGROUND OF THE INVENTION

In a typical communication system, such as the Internet, it is possible to visit a location within the system, store the location (e.g. "bookmark" the location) and then return to that location at a later time. For example, 15 Microsoft™ Internet Explorer allows a user to access a given web site, bookmark the site and then return to the same site at a later time. Once bookmarked, the user may easily access the site, usually by selecting the bookmark from a stored list of bookmarks (in Internet Explorer this list is typically called "Favorites".)

20

In a typical communication system, it is also possible to enter location data for more than one location, store the data and then access the data at a later time. For example, Yahoo™ allows a user to enter one or more street addresses (such as a pair of cross-streets) on a web page, store the entered data (e.g. "bookmark" the data) and then access the data at a later time.

25

Once bookmarked, the user may easily access the data, usually by selecting the bookmark from a stored list of bookmarks (in Yahoo™, this list is typically called "My Locations").

30

In a wireless communication system, it may also be possible to obtain immediately pertinent information in relation to bookmarked data. For example, a user may obtain information about a stored street address such as directions from the address or current weather conditions at the address.

However, typical communication systems have limited capabilities. It would be desirable therefore to provide a method additional capabilities for a communications system.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating a communication system in which the invention can be implemented;

5 **FIG. 2** is a flow chart illustrating a routine for storing a relationship between two points;

FIG. 3 is a flow chart illustrating a routine for accessing a relationship stored using the embodiment of **FIG. 2**;

10 **FIG. 4** is a flow chart illustrating another routine for accessing a relationship stored using the embodiment of **FIG. 2**;

FIG. 4 is a flow chart illustrating another routine for accessing a relationship stored using the embodiment of **FIG. 2**;

FIG. 5 is a flow chart illustrating another routine for accessing a relationship stored using the embodiment of **FIG. 2**; and

15 **FIG. 6** is an exemplary block diagram illustrating another embodiment of a communication system.

DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

20

A system and method permit saving of a route between an originating location and a destination. The route may be identified by a first location and a second location. A route-identifier is used to identify a route between the first location and the second location, and route identifier is stored. The route
25 identifier is used to retrieve the route. Typical communications systems do not allow the ability to select more than one location, save the relationship between the selected locations and then return to the relationship at a later time. Typical communications systems also do not allow the ability to obtain pertinent information about the relationship at a later time. In particular, a
30 typical communication system does not allow selection of a first location and one or more additional location to create a route that may then be bookmarked.

FIG. 1 is a block diagram illustrating one embodiment of a communication system **10**. The communication system **10** generally includes

one or more network access devices or communication devices **12, 32**, communication networks **14, 18** and a communication node **16**. The communication system **10** may also include one or more of each of the following: route application **64**, route database **62**, geographic source **60** and
5 information source **58**.

As further described below, the communication system **10** may provide various services and capabilities to cellular users, wire-line telephone users, paging users, satellite users, mobile or portable telephone users, trunked users, computer network users (e.g., Internet or Intranet users), wireless data
10 users, branch office users, cable users and the like. Communication system **10** may also accurately locate communication device **12, 32** and/or its associated user **20, 30** in order to provide location-relevant services to the user **20, 30** via device **12, 32**. Communication system **10** may also accurately locate any relevant location in order to provide services to the user **20, 30** via
15 device **12, 32**. Communication system **10** or any of its components may be operated by any entity, including, without limitation, a government agency, a commercial entity, or any other appropriate entity.

In one embodiment of the invention, communication system **10** also includes a route application **64**. Route application **64** may include one or
20 more programs or other applications for creating and otherwise processing information about two or more points, such as geographic points, or information about routes between two or more points. Route application **64** may comprise computer readable/processable program code. Such route information may be information input by user **20, 30** via device **12, 32**. Route
25 application **64** may also process information to be sent to or stored in route database **62**. Alternatively, route information processed by route application **64** may be information provided by communication node **16** or forwarded by communication node **16** from communication networks **14, 18**. Route information processed by route application **64** may also be provided by
30 information sources such as route database **62** or geographic source **60**. Route application **64** may interact with user **20, 30** via device **12, 32**. Route application **64** may reside on or be in communication with communication node **16** or communication device **12, 32**.

Route application **64** may process information from one or more information sources. One such information source is route database **62**. In one embodiment of the present invention, route database **62** stores geographic locations in the form of routes between two or more geographic locations. For example, a user may send a geographic location such as the route between two or more street addresses (e.g. "Route from Home to Work") to be stored in route database **62**. The user may input the location to be stored from a communication device **12, 32** via communication node **16**.

Route database **62** may contain an identifier and associated route information. For example, route database **62** may contain the identifier "HOME/WORK" and the route information "starting point: 3200 N. Clark Street, Chicago, Illinois 60657 and endpoint point: 1603 Orrington Avenue, Evanston, Illinois 60201" as one entry. The data stored in route database **62** may also take other forms including, but not limited to, latitude/longitude, points of interest or intersections. For example, the route and identifier above may also take the format "HOME/WORK" and associated route information "first endpoint: Belmont and Clark, Chicago and second endpoint: Orrington and Davis, Evanston, Illinois". The data stored in route database **62** may also store information in a combination of forms. For example, the route and identifier above may also take the form "HOME/WORK" and associated route information "endpoint 1: Belmont and Clark, Chicago and endpoint 2: Bank One Building, Evanston, Illinois."

Route application **64** may also process information from one or more information sources such as geographic source **60**. In one embodiment of the present invention, geographic source **60** stores authentic ("real") geographic locations. Alternatively, this geographic source **60** authenticates, verifies or otherwise processes information about to be stored or already stored in route database **62**. For example, a user may send a route such as those described above to be stored in route database **62**. Before the route is accepted to be stored, communication system **10** authenticates or otherwise processes the address using geographic source **60**. For example, geographic source **60** may be a GIS engine that authenticates each of the addresses in a given route as existing addresses. In one embodiment of the invention, geographic source **60** may authenticate that the route is accurate, e.g. the user desires to

store the route between his home and a hotel in Seattle but the geographic source 60 indicates the hotel is no longer at the location entered by the user. In another embodiment, geographic source 60 may complete or correct the location input by the user, verifying that the address is authentic and unambiguous and completing the address with the zip code or zip + 4. For example, the user says "endpoint 1 is Belmont and Clarke, spelled C-L-A-R-K-E, Chicago, Illinois and endpoint 2 is the Bank One Building, Evanston, Illinois" and the geographic source provides the corrected information that the first endpoint is "Belmont and Clark, spelled C-L-A-R-K Chicago, Illinois 60657" and the completed information that the second endpoint is "Bank One Building, Evanston, IL 60201." The user may input the route to be stored from a communication device 12, 32 via communication node 16.

In one embodiment, geographic source 60 may comprise authentic ("real") cellular and sector identification information. Geographic source 60 may also include maps relating to such cellular and sector identification information. Geographic source 60 may also include geographical and non-geographical information about countries, states/provinces, counties/parishes, metropolitan areas, cities, ZIP codes, area codes, landmarks, points of interest, subway and train stations, airports, streets, gas stations, Automated Teller Machines (ATMs), hospitals, police stations, restaurants, etc. In one embodiment, geographic source 60 may comprise a virtual map of a given area, complete with a listing of all geographical entities on the map, such as a listing of all streets within Chicago, Illinois, for example. Geographic source 60 may also include such information as specific names and addresses (e.g. a list of hospital names and their addresses) or a more general address listing (e.g. an electronic "yellow pages").

Location parameters that may be corrected, completed or otherwise processed using information from geographic source 60 include, but are not limited to: lists of streets within a city; lists of streets within a cell or sector; lists of streets within a state; lists of street names and numbers; zip code lists; lists of street intersections; lists of landmarks in a given city, state, cell or sector; lists of places of interests in a given city, state, cell or sector; lists of banks in a given city, state, cell or sector; lists of restaurants in a given city, state, cell or sector; lists of hotels in a given city, state, cell or sector; lists of

post offices in a given city, state, cell or sector; lists of businesses of a given type in a given city, state, cell or sector, etc.

Route application **64** may also process information from one or more other information sources **58**. In one embodiment of the present invention, information source **58** stores information that may be relevant to a given route. Such information includes, but is not limited to, traffic conditions, weather conditions, upcoming conditions along the way (e.g., toll booths coming up on the route), relevant locations on the route (e.g., restaurants along the route, banks along the route.) For example, a user may send a route such as those described above to be stored in route database **62**. Before the route is accepted to be stored or after the route has been stored, communication system **10** may provide information about the route using information source **58**. For example, information source **58** may provide up-to-date weather conditions for the area encompassing user's "HOME/WORK" route or, if the route covers a large area, weather conditions for portions of the route. Alternatively, information source **58** may provide traffic conditions at points along the route. Alternatively, information source **58** may provide information about a third point on the route, e.g., the location of a toll booth on the route, the McDonalds™ nearest to the first endpoint of the route, or the name of the bank closest to the second endpoint of the route. Alternatively, if the user is currently on the route, information source may provide information about the user's location on the route, e.g. weather conditions for the user's current location on the route.

Information source **58** may be, for example, a web site on the Internet in communication with or accessed by communication system **10** or a component of system **10**. Information source **58** may also be a service, such as a weather service in communication with or accessed by communication system **10** or a component of system **10**, e.g. the National Weather Service.

The communication device **12, 32** of the communication system **10** may be utilized by end user **20, 30** to access and/or connect with the communication node **16**. Communication device **12, 32** may also be used by end user **20, 30** to access and/or connect with route application **64**. The communication device **12, 32** can include, but is not limited to, wireline telephones, mobile telephones, paging units, radio units, wireless data

devices, Web telephones, portable or wireless telephones, personal information managers (PIMs), personal digital assistants (PDAs), personal computers (PCs), network televisions (TVs), Internet TVs, Internet telephones, portable wireless devices (i.e., two-way pagers), security systems
5 (both mobile and premises-based), workstations or any other suitable communication devices.

Regardless of its specific form, the communication devices **12, 32** have user-input interfaces **24, 28** and/or user-output interfaces **34, 38**. Alternatively, the user-input interfaces **24, 28** and/or user-output interfaces **34,**
10 **38** may work in conjunction with the communication device **12, 32** without actually residing on the device **12, 32**.

The user-input interfaces **24, 28** may receive input from the users **20, 30** and the user-output interfaces **34, 38** may provide output to the users **20, 30**. The user-input interfaces **24, 28** can include, but are not limited to, an
15 electroacoustic transducer, such as, for example, a microphone to receive voice and other audible input from the users **20, 30** a keypad or a keyboard to receive key strokes from the users **20, 30** a touchpad or touchscreen to receive touch input from the users **20, 30** a handwriting recognition interface to receive handwritten input from users **20, 30** and a pointing device such as a
20 mouse or a trackball to receive point and click inputs from the users **20, 30**. In one embodiment of the present invention, user-input interface **24, 28** may be a modified car dashboard allowing input from users **20, 30**.

The user-output interfaces **34, 38** of the communication devices **12, 32** can include, but are not limited to, an electroacoustic transducer such as, for
25 example, a speaker to provide voice and other audible output to the users **20, 30**, and a visual display device such as a liquid crystal display or a cathode ray tube to provide graphical and/or textual information to the users **20, 30**. In one embodiment of the present invention, user-output interface **34, 38** may be a modified car dashboard providing output to users **20, 30**.

Each of the communication devices **12, 32** may include more than one user-input interface **24, 28** or more than one user-output interface **34, 38**. Moreover, the user may use one or more user-input interfaces **24, 28** or user-output interfaces **34, 38** simultaneously. For example, a wireless

telephone may have a microphone, a telephone keypad, a speaker, and a visual display device.

In one embodiment of the invention, an input interface **24, 28** may also reside on the communication node **16**. Output interface **34, 38** may also
5 reside on the communication node **16**. Alternatively, input interface **24, 28** may reside on the communication node **16** while output interface **34, 38** resides on the device **12, 32**. Alternatively, input interface **24, 28** may reside on the device **12, 32** while output interface **34, 38** resides on communication node **16**.

10 The communication device **12, 32** may also communicate with communication networks **14, 18** via the communication node **16**. The communication network **14** can interface with the communication device **12, 32** through wireline or wireless networks or systems (i.e., telephone or televisions systems, Integrated Services Digital Network (ISDN) systems,
15 coaxial lines, computer networks, digital end user lines, private networks, wireless local loop systems, etc.). Information sources **58** may be accessible to, available on or in communication with communication networks **14, 18**.

The communication networks **14, 18** of the communication system **10** can include, but are not limited to, intranets, extranets, the Internet, a Local
20 Area Network (LAN), a telephone network, (e.g., a Public Switched Telephone Network (PSTN), private telephone networks, etc.), a cellular network, satellite networks, a personal communication system, a TV network (e.g., a cable TV system), local, regional, national or global paging networks, an email system,
25 a wireless data network (e.g., satellite data or local wireless data networks), a wireless LAN, a wireless local loop/distribution system (e.g., LMDS, MMDS or Code Division Multiple Access (CDMA) based system), a Voice Over Internet Protocol (VOIP) network, or any other suitable network. The communication networks **14, 18** can also include a wide area network (WAN), such as, for
30 example, the Internet, the World Wide Web (WWW) or any other similar on-line service. It will be recognized that the communication networks **14, 18** may have portions in common, may comprise two separate networks, or may be the same network.

The communication node **16** of the communication system **10** can include, but is not limited to, an interactive voice response node, a server

computer, the MIX™ platform and the Myosphere™ Service provided by Motorola, Inc. of Schaumburg, IL (as further described with reference to **FIG. 6**), or other suitable system. It will be recognized that the communication node **16** may be integrated within or may be remote from the communication networks **14, 18**.

FIG. 2 illustrates one embodiment of a routine for storing a relationship between two points in accordance with the present invention at **2000**. The routine of **FIG. 2** may be used, for example, when a user **20, 30** first attempts to store a relationship between two or more points, such as a travel route between two locations.

At block **2010** an input signal is received describing the route. This input signal may take the form of data describing a starting point and an endpoint. For example, the user may say "Identify 'Belmont and Clark, Chicago, Illinois' as the start point and 'Davis and Orrington, Evanston, Illinois' as the endpoint of a route called "HOME/WORK". The input signal may also take the form of data describing versions of the route (e.g. fastest version, scenic version, version of route using the shortest distance, version without any highways, version of route with no tolls). For example, the user may say "Identify the route between 3200 North Clark in Chicago, Illinois and 1600 Orrington Avenue in Evanston, Illinois which uses Lake Shore Drive as 'HOME/WORK-FATEST".

At Block **2020**, the action to be taken determines which routine may be used in accordance with the present invention. For example, **FIG. 2** shows three possible actions: GET INFORMATION, ADD and MODIFY. These three actions serve as examples and do not limit the actions that may be taken in accordance with the present invention.

In the case of adding a route to be stored, at block **2030** a route identifier may be received. This identifier may be included in the initial input signal transmitted at Blocks **2010**. Alternatively, the route identifier may be sent separately.

At Block **2035** the uniqueness of the route identifier is evaluated. In one embodiment, this evaluation is performed by route application **64**. Alternatively, this evaluation is performed by node **16** or by route application

64 on node 16. In one embodiment this evaluation includes a determination by route application 64 of whether or not the route identifier is already in use. If the route identifier is already in use (as seen at 2037) another route identifier may be received as illustrated at 2030. If the route identifier is already in use, the communication node 16 may indicate to user 20, 30 that a new route identifier should be chosen.

In one embodiment, the user is prompted to confirm the route identifier received at Block 2030. In another embodiment the identifier may be provided to the user and then confirmed. Alternatively, the route identifier may be generated by route application 64, by communication node 16 or another party, such as a system administrator.

If the route identifier received at Block 2030 is not currently in use or is otherwise determined to be unique, the route associated with the route identifier may be processed (Block 2050). For example, the points of the route may be processed (e.g., converted to an appropriate format such as a latitude and longitude). Such processing may also include encrypting the route identifier and associated route or any other suitable processing. Such processing may also include adding further information to the route identifier and its associated route. For example, processing may include completing geographic information related to the points of the route, e.g. adding a zip code or a zip+4 to the addresses associated with one or more points of the route. As another example, processing may include adding a route type describing the associated route (e.g. fastest route, shortest route, scenic route).

Then at block 2060, the route identifier and its associated route may be stored in any suitable manner, such as, for example, in a database in communication with communication node 16 or device 12, 32.

During the time the route and route identifier are being processed, a signal may be sent to the user, for example via the browser of device 12, 32. This signal may contain one or more commands to the browser of device 12, 32. In one embodiment of the invention, the signal may be sent via node 16. Alternatively, the signal may be sent directly from route application 64. In one embodiment of the invention, device 12, 32 may tell the user "Route 'HOME/WORK' being stored" during this time period.

Once the route identifier and associated route have been stored, the route application **64** may send a response to the user **20, 30**. This response may contain one or more commands. For example, device **12, 32** may say "Route 'HOME/WORK' has been stored". Device **12, 32** may also prompt
5 "Store route 'HOME/WORK' now?" or may ask additional information from the user, such as "Is this the fastest route between Home and Work?"

FIG. 3 illustrates one embodiment of a routine for retrieving information relevant to a route in accordance with the present invention at **3000**. The routine of **FIG. 3** may begin with the input signal being received as illustrated
10 at Block **2010** of **FIG. 2**. Alternatively, the routine of **FIG. 3** may begin after a route identifier has already been stored as illustrated at block **2060**.

At Block **3030** of **FIG. 3**, the route identifier may be received. The identifier may be, for example, a suitable route identifier as described above. At block **3035**, a request for information about the route identified by the route
15 identifier may also be received. For example, the user may request "Tell me current traffic conditions on route "HOME/WORK". The request may also further describe the version of the route identified by the route identifier. For example, the user may say "Access fastest route for "HOME/WORK". In **FIG. 3**, the steps shown at **3030** and **3035** may occur in any suitable order.

Then, at Block **3040**, it may be determined if the route identifier has been stored within system **100**. For example, it may be determined if the route identifier has been stored in route database **62**. Such a route identifier may have been stored, for example, as indicated at Block **2060** of **FIG. 2**. If the route identifier has been stored, the information associated with the route
20 identifier may then be retrieved at block **3050**. Alternatively, if the route identifier has not previously been stored, the routine may return to **3030** as shown in **FIG. 3**. Another identifier may then be received.

Once the route information has been retrieved at block **3050**, as seen at block **3060**, information relevant to the route may be retrieved. This route-relevant information may be stored in any suitable location and may be
30 accessed by any suitable component of system **100**. For example, the route-relevant information may be stored in information source **58** or geographic source **60**. In one example, information about the current traffic conditions may be retrieved from a traffic database or a news service. The

route-relevant information may also be dynamically created information rather than accessed information. For example, the route-relevant information may be a calculation of the shortest version of the route identified by the route identifier. Alternatively, the information relevant to the route may be a combination of accessed and dynamically created information. For example, the information provided may be traffic conditions for various roads that can be used to complete the route identified by the route identifier.

At block **3070**, the retrieved information may be presented. For example, the user may hear "There is an accident at 5600 North Clark on route 'HOME/WORK'." The user may also hear "There is an accident on the shortest distance route of 'HOME/WORK'. Would you like to determine an alternative 'HOME/WORK' route?"

FIG. 4 illustrates another embodiment of a routine for retrieving information relevant to a route in accordance with the present invention at **4000**. The routine of **FIG. 4** may begin with the input signal being received as illustrated at Block **2010** of **FIG. 2**. Alternatively, the routine of **FIG. 4** may begin after a route identifier has already been stored as illustrated at block **2060**.

At Block **4030** of **FIG. 4**, the route identifier may be received. The identifier may be, for example, a suitable route identifier as described above. At block **4035**, a location identifier may also be received. This location identifier may be any suitable identifier that describes a location along the route identified by the route identifier. In one embodiment of the invention, the location identifier describes a third point between the starting point and ending point of the route identified by the route identifier. For example, the location identifier may identify where a mobile user is currently located on the route "HOME/WORK", e.g. "My location is about 3 miles from the starting point of route "HOME/WORK". This location identifier may be input by the user **20, 30**. The location identifier may also be input by another entity, such as, for example, a global positioning device on the user's car. In **FIG. 4**, the steps shown at **4030** and **4035** may occur in any suitable order.

Then, at Block **4040**, it may be determined if the route identifier has been stored within system **100**. For example, it may be determined if the route identifier has been stored in route database **62**. Such a route identifier

may have been stored, for example, as indicated at Block **2060** of **FIG. 2**. If the route identifier has been stored, the information associated with the route identifier may then be retrieved at block **4050**. Alternatively, if the route identifier has not previously been stored, the routine may return to **4030** as shown in **FIG. 4**. Another identifier may then be received.

Once the route information has been retrieved at block **4050**, as seen at block **4060**, information relevant to the location identified by the location identifier may be retrieved. This location-relevant information may be stored in any suitable location and may be accessed by any suitable component of system **100**. For example, the location-relevant information may be stored in information source **58** or geographic source **60**. In one embodiment, information about the current traffic conditions may be retrieved from a traffic database or a news service. For example, the traffic conditions for a point five miles from the ending point of route "HOME/WORK" may be provided to the user. In another embodiment, the location of other objects in relation to the location identified by the location identifier may be provided in the context of the route identified by the route identifier. For example, the location of the toll booth nearest to the mobile user's current location may be provided in the context of the route the user is on.

At block **4070**, the retrieved information may be presented. For example, the user may hear "Traffic is clear from your current location all the way to the HOME point of route 'HOME/WORK'." The user may also hear "The nearest toll booth to your current location is another two blocks along the route 'HOME/WORK'."

FIG. 5 illustrates one embodiment of a routine for modifying the stored route information in accordance with the present invention at **4000**. The routine of **FIG. 5** may begin with the input signal being received as illustrated at Block **2010** of **FIG. 2**. Alternatively, the routine of **FIG. 5** may begin after a route identifier has already been stored as illustrated at block **2060**.

At Block **5030** of **FIG. 5**, the route identifier may be received. The identifier may be, for example, a suitable route identifier as described above.

Then, at Block **5040**, it may be determined if the route identifier has been stored within system **100**. For example, it may be determined if the route identifier has been stored in route database **62**. Such a route identifier

may have been stored, for example, as indicated at Block **2060** of **FIG. 2**. If the route identifier has not previously been stored, the routine may return to block **5030** as shown in **FIG. 5**. Another identifier may then be received.

- If the route identifier has been stored, a decision may be made to
- 5 modify the route identifier at block **5050**. If the route identifier will not be modified, the routine may return to block **5030** as shown in **FIG. 5**. Another identifier may then be received. If the route identifier will be modified, a modified route identifier is received at **5060**.

- At Block **5070** the uniqueness of the modified route identifier is
- 10 evaluated. In one embodiment, this evaluation is performed by route application **64**. Alternatively, this evaluation is performed by node **16** or by route application **64** on node **16**.

- If the route identifier received at Block **5070** is not currently in use or is otherwise determined to be unique, the route associated with the modified
- 15 route identifier may be processed (Block **5090**). For example, the points of the route may be processed (e.g., converted to an appropriate format such as a latitude and longitude). Such processing may also include encrypting the modified route identifier and associated route or any other suitable processing. Such processing may also include adding further information to
- 20 the modified route identifier and its associated route. For example, processing may include completing geographic information related to the points of the route, e.g. adding a zip code or a zip+4 to the addresses associated with one or more points of the route.

- Then at block **2095**, the modified route identifier and its associated
- 25 route may be stored in any suitable manner, such as, for example, in a database in communication with communication node **16** or device **12, 32**.

Referring now to **FIG. 5**, an exemplary block diagram of another embodiment of a communication system **200** having the capability to bookmark a route between two or more locations is illustrated.

- 30 The communication system **200** generally includes one or more communication devices **201, 202, 203, 204, 205** (five being shown), an electronic network **206**, and one or more information sources (e.g., content providers **208, 221** (two being shown) and data and voice markup language servers **209, 251, 253, 257**).

The user can access the electronic network **206** by dialing a single direct access telephone number (e.g., a foreign telephone number, a local telephone number, or a toll-free telephone number or PBX) from the communication device **201**. The user can also access the electronic network

5 **206** from the communication device **202** via the Internet **220** or WWW, from the communication device **203** via a paging network **211**, or from the communication device **205** via a LAN, a WAN, an e-mail connection or in any other similar manner.

As shown in **FIG. 5**, the electronic network **206** includes a

10 telecommunication network **210** and a communication node **212**. The telecommunication network **210** is preferably connected to the communication node **212** via a high-speed data link, such as, for example, a T1 telephone line, a LAN, a WAN or a VOIP network. The telecommunication network **210** preferably includes a PSTN **214** and a carrier network **216**. The

15 telecommunication network **210** can also include, for example, international or local exchange networks, cable TV networks, inter-exchange carrier or long distance carrier networks, cellular networks (e.g., mobile switching centers), PBXs, satellite systems, wireless data networks and other switching centers such as conventional or trunked radio systems (not shown), etc. The

20 electronic network **206** can also include additional telecommunication networks, such as, for example, a wireless data network **207**.

The PSTN **214** can include various types of communication equipment, such as, for example, ATM networks, Fiber Distributed Data networks (FDDI), T1 lines, cable TV networks, VOIP networks and the like. The carrier network

25 **216** generally includes a telephone switching system or central office **218**.

It will be recognized that the carrier network **216** can be any suitable system that can route calls to the communication node **212**, and the central office **218** can be any suitable wire-line or wireless switching system.

The communication node **212** is preferably configured to receive and

30 process incoming calls from the carrier network **216** and the Internet **220**. The communication node **212** can receive and process pages from the paging network **211** and can also receive and process messages (e.g., e-mails) from the LAN, WAN, wireless data or e-mail system **213**.

When a user dials into the electronic network **206** from the communication device **201**, the carrier network **216** routes the incoming call from the PSTN **214** to the communication node **212** over one or more telephone lines or trunks. The incoming calls preferably enter the carrier network **216** through one or more "888" or "800" Inward Wide Area Telecommunications Services trunk lines, local exchange or long distance trunk lines. It is also contemplated that the incoming calls can be received from a cable, cellular or VOIP network or any other suitable system.

The communication node **212** answers the incoming call from the carrier network **216** and retrieves an appropriate announcement (e.g., a welcome greeting) from a database, server or browser. The communication node **212** then plays the announcement to the caller. In response to audio inputs from the user, the communication node **212** retrieves information from a destination or database of one or more of the information sources, such as the content providers **208, 221** or the markup language servers **209, 251, 253, 257**. After the communication node **212** receives the information, it provides a response to the user based upon the retrieved information.

The communication node **212** can provide various dialog voice personalities (e.g., a female voice, a male voice, etc.), and can implement various grammars (e.g., vocabulary) to detect and respond to the audio inputs from the user. In addition, the communication node **212** can automatically select various speech recognition models (e.g., English, Spanish or English accent models) based upon a user's profile, communication device and/or speech patterns. The communication node **212** can also allow the user to select a particular speech recognition model.

When a user accesses the electronic network **206** from a communication device **201, 202, 203, 204, 205** registered with the system (e.g., home telephone, work telephone, cellular telephone, etc.), the communication node **212** can by-pass a user screening option and automatically identify the user (or the type of communication device) through the use of ANI or CLI. After the communication node **212** verifies the call, the communication node **212** provides a greeting (e.g., "Hi, this is your personal agent, Mya. Welcome Bob. How may I help you?"). The communication

node **212** then enters into a dialogue with the user, and the user can select a variety of services offered by the communication node **212**.

When the user accesses the electronic network **206** from a communication device not registered with the system (e.g., a payphone, a telephone of a non-user, etc.), the communication node **212** answers the call and prompts the user to enter his or her name and/or a personal identification number (PIN) using voice commands or DTMF signals. The communication node **212** can also utilize speaker verification to identify the particular speech pattern of the user. If the communication node **212** authorizes the user to access the system, the communication node **212** provides a personal greeting to the user (e.g., "Hi, this is your personal agent, Mya. Welcome Ann. How may I help you?"). The communication node **212** then enters into a dialogue with the user, and the user can select various services offered by the communication node **212**. If the name and/or PIN of the user cannot be recognized or verified by the communication node **212**, the user will be routed to a customer service representative.

Once the user has accessed the communication system **200**, the user may implement a wide variety of services and features by using voice commands, such as, for example, voice dialing, voice paging, facsimiles, caller announcements, voice mails, reminders, call forwarding, call recording, content information (e.g., newspapers, etc.), read e-mail, read calendars, read "to-do" lists, banking, e-commerce. The communication system **200** can place outbound calls and pages to business and personal parties or contacts (e.g., friends, clients, business associates, family members, etc.) in response to DTMF signals or voice commands. The calls can be routed through a telephone or electronic network to the selected party and the pagers can be sent to a selected party via a paging system. The communication system **200** can also receive calls routed through a telephone or electronic network.

As shown in **FIG. 5**, the communication node **212** preferably includes a telephone switch **230**, a voice or audio recognition (VRU) client **232**, a VRU server **234**, a controller or call control unit **236**, an Operation and Maintenance Office or a billing server unit **238**, a LAN **240**, an application server unit **242**, a database server unit **244**, a gateway server or router firewall server unit **246**, a VOIP unit **248**, a voice browser **250**, a voice markup language server **251**, a

messaging server **255** and a data markup language server **253**. Although the communication node **212** is shown as being constructed with various types of independent and separate units or devices, the communication node **212** can be implemented by one or more integrated circuits, microprocessors, microcontrollers or computers which may be programmed to execute the operations or functions equivalent to those performed by the devices or units shown. It will also be recognized that the communication node **212** can be carried out in the form of hardware components and circuit designs and/or software or computer programs.

10 The communication node **212** can be located in various geographic locations throughout the world or the United States (e.g., Chicago, IL). The communication node **212** can be operated by one or more carriers (e.g., Sprint, Qwest, MCI, etc.) or independent service providers (e.g., Motorola, Inc.).

15 The communication node **212** can be integrated with the carrier network **216** or can be located remote from the carrier network **216**. It is also contemplated that the communication node **212** may be integrated into a communication device, such as, for example, a wire-line or wireless telephone, a radio device, a PC, a PDA, a PIM, etc., and can be programmed to connect or link directly to an information source.

20 The communication node **212** can also be configured as a standalone system to allow users to dial directly into the communication node **212** via a direct access telephone number. In addition, the communication node **212** may comprise a telephony switch (e.g., a PBX or Centrix unit), an enterprise network or a LAN. In this configuration, the communication system **200** can be implemented to automatically connect a user to the communication node **212** when the user accesses a communication device.

25 When the telephone switch **230** receives an incoming call from the carrier network **216**, the call control unit **236** sets up a connection in the telephone switch **230** to the VRU client **232**. The communication node **212** then enters into a dialog with the user regarding various services and functions. The VRU client **232** preferably generates pre-recorded voice announcements and/or messages to prompt the user to provide inputs to the communication node **212** using voice commands or DTMF signals. In

response to the inputs from the user, the communication node **212** retrieves information from a destination of one of the information sources and provides outputs to the user.

- The telephone switch **230** is preferably connected to the VRU client
- 5 **232**, the VOIP unit **248** and the LAN **240**. The telephone switch **230** receives incoming calls from the carrier network **216**. The telephone switch **230** also receives incoming calls from the communication device **202** routed over the Internet **220** via the VOIP unit **248**. The telephone switch **230** also receives messages and pages from communication devices **203**, **205**, respectively.
- 10 The telephone switch **230** is preferably a digital cross-connect switch, Model LNX, available from Excel Switching Corporation, Hyannis, MA. It will be recognized that the telephone switch **230** can be any suitable switch.

- The VRU client **232** is preferably connected to the VRU server **234** and the LAN **240**. The VRU client **232** processes voice communications, DTMF
- 15 signals, pages and messages (e.g., e-mails). Upon receiving voice communications, the VRU client **232** routes the speech communications to the VRU server **234**. When the VRU client **232** detects DTMF signals, it sends a command to the call control unit **236**. It will be recognized that the VRU client **232** can be integrated with the VRU server **234**.

- 20 The VRU client **232** preferably comprises a PC, such as, for example, a Windows NT compatible PC, with hardware capable of connecting individual telephone lines directly to the telephone switch **230** or carrier network **216**. The VRU client **232** preferably includes a microprocessor, random access memory, read-only memory, a T1 or ISDN interface board, and one or more
- 25 voice communication processing boards (not shown). The voice communication processing boards are preferably Dialogic boards, Antares Model, available from Dialogic Corporation, Parsippany, NJ. The voice communication boards may include a voice recognition engine having a vocabulary for detecting a speech pattern. The voice recognition engine is
- 30 preferably a RecServer software package, available from Nuance Communications, Menlo Park, CA.

The VRU client **232** can also include an echo canceller (not shown) to reduce or cancel TTS or playback echoes transmitted from the PSTN **214** due

to hybrid impedance mismatches. The echo canceller is preferably included in an Antares Board Support Package, also available from Dialogic.

The call control unit **236** is preferably connected to the LAN **240**, and sets up the telephone switch **230** to connect incoming calls to the VRU client

- 5 **232**. The call control unit **236** also sets up incoming calls or pages to the communication node **212** over the Internet **220** and pages and messages sent from the communication devices **203**, **205** via the paging network **211** and e-mail system **213**, respectively. The control call unit **236** preferably comprises a PC, such as, for example, a Windows NT compatible PC.

- 10 The LAN **240** allows the various components and devices of the communication node **212** to communicate with each other via twisted pair, fiber optic, coaxial cables or the like. The LAN **240** may use Ethernet, Token Ring or other suitable types of protocols. The LAN **240** is preferably a **100** Megabit per second Ethernet switch, available from Cisco Systems, San Jose, CA, and can comprise any suitable network system. The communication
- 15 node **212** may include a plurality of LANs.

- The VRU server **234** is connected to the VRU client **232** and the LAN **240**. The VRU server **234** receives voice communications from the user via the VRU client **232**. The VRU server **234** processes the voice
- 20 communications and compares the voice communications against a vocabulary or grammar stored in the database server unit **244** or a similar memory device. The VRU server **234** provides output signals, representing the result of the voice communications processing, to the LAN **240**. The LAN **240** routes the output signal to the call control unit **236**, the application server
- 25 unit **242** and/or the voice browser **250**. The communication node **212** then performs a specific function associated with the output signals.

- The VRU server **234** preferably includes a TTS unit **252**, an automatic speech recognition (ASR) unit **254**, and a STT unit **256**. The TTS unit **252** receives textual data or information (e.g., e-mail, web pages, documents, files,
- 30 etc.) from the application server unit **242**, the database server unit **244**, the call control unit **236**, the gateway server unit **246**, the application server unit **242** and the voice browser **250**. The TTS unit **252** processes the textual data and converts the data to voice data or information.

The TTS unit **252** can provide data to the VRU client **232**, which reads or plays the data to the user. For example, when the user requests information (e.g., news updates, stock information, traffic conditions, etc.), the communication node **212** retrieves the desired data (e.g., textual information) from a destination of the one or more of the information sources and converts the data via the TTS unit **252** into a response.

The response is then sent to the VRU client **232**. The VRU client **232** processes the response and reads an audio message to the user based upon the response. It is contemplated that the VRU server **234** can read the audio message to the user using human recorded speech or synthesized speech. The TTS unit **252** is preferably a TTS **2000** software package, available from Lernout and Hauspie Speech Product NV, Burlington, MA.

The ASR unit **254** provides speaker dependent or independent automatic voice recognition of voice communications from the user. It is contemplated that the ASR unit **254** can include speaker dependent voice recognition. The ASR unit **254** processes the voice communications to determine whether a word or a speech pattern matches any of the grammars or vocabulary stored in the database server unit **244** or downloaded from the voice browser **250**. When the ASR unit **254** identifies a selected speech pattern of the voice communications, the ASR unit **254** sends an output signal to implement the specific function associated with the recognized speech pattern. The ASR unit **254** is preferably a speaker independent voice recognition software package, RecServer Model, also available from Nuance Communications. It is contemplated that the ASR unit **254** can be any suitable voice recognition unit to detect voice communications.

The STT unit **256** receives voice communications and converts the voice communications to textual information (e.g., a text message). The textual information can be sent or routed to the communication devices **201**, **202**, **203**, **204**, **205**, the content providers **208**, **221**, the markup language servers **209**, **251**, **253**, **257**, the voice browser **250** and the application server unit **242**. The STT unit **256** is preferably a Naturally Speaking software package, available from Dragon Systems, Newton, MA.

The VOIP unit **248** is preferably connected to the telephone switch **230** and the LAN **240**. The VOIP unit **248** allows a user to access the

communication node **212** via the Internet **220** or VOIP public network using voice commands. The VOIP unit **248** can receive VOIP protocols (e.g., H.323 protocols) transmitted over the Internet **220** or Intranet, and can convert the VOIP protocols to voice information or data. The voice information can then be read to the user via the VRU client **232**. The VOIP unit **248** can also receive voice communications from the user and convert the voice communications to a VOIP protocol that can be transmitted over the Internet **220**. The VOIP unit **248** is preferably a Voice Net software package, also available from Dialogic Corporation. It will be recognized that the VOIP unit **248** can be incorporated into a communication device.

The communication node **212** also includes a detection unit **260**. The detection unit **260** is preferably a phrase or key word spotter unit, detecting incoming audio inputs or communications or DTMF signals from the user. The detection unit **260** is preferably incorporated into the telephone switch **230**, but can be incorporated into the VRU client **232**, the carrier network **216** or the VRU server **234**. The detection unit **260** is preferably included in a RecServer software package, also available from Nuance Communications.

The detection unit **260** records the audio inputs from the user and compares the audio inputs to the vocabulary or grammar stored in the database server unit **244**. The detection unit **260** continuously monitors the user's audio inputs for a key phrase or word after the user is connected to the node **212**. When the detection unit **260** detects the key phrase or word, the VRU client **232** plays a pre-recorded message to the user. The VRU client **232** then responds to the audio inputs provided by the user.

The billing server unit **238** is preferably connected to the LAN **240**. The billing server unit **238** can record data about the use of the communication node **212** by a user (e.g., length of calls, features accessed by the user, etc.). Upon completion of a call by a user, the call control unit **236** sends data to the billing server unit **238**. The billing server unit **238** can subsequently process the data in order to prepare customer bills. The billing server unit **238** can use the ANI or CLI of the communication device to properly bill the user. The billing server unit **238** preferably comprises a Windows NT compatible PC.

The gateway server unit **246** is preferably connected to the LAN **240** and the Internet **220**. The gateway server unit **246** provides access to the

content provider **221** and the voice markup language server **257** via the Internet **220**. The gateway server unit **246** allows users to access the communication node **212** from the communication device **202** via the Internet **220**. The gateway server unit **246** can function as a firewall to control access to the communication node **212** to authorized users. The gateway server unit **246** is preferably a Cisco Router, also available from Cisco Systems.

The database server unit **244** is preferably connected to the LAN **240**. The database server unit **244** preferably includes a plurality of storage areas to store data relating to users, such as, for example, speech vocabularies, dialogs, personalities, user entered data, and other information. Preferably, the database server unit **244** stores a personal file or address book. The personal address book can contain information required for the operation of the communication system **200**, including user reference numbers, personal access codes, personal account information, contact's addresses, telephone numbers, etc. The database server unit **244** is preferably a PC, such as, for example, a Windows NT compatible PC.

The application server unit **242** is preferably connected to the LAN **240** and the content provider **208**. The application server unit **242** allows the communication node **212** to access information from a destination of the information sources, such as the content providers **208**, **221** and the markup language servers **209**, **251**, **253**, **257**. For example, the application server unit **242** can retrieve information (e.g., weather reports, stock information, traffic reports, restaurants, flower shops, banks, calendars, "to-do" lists, e-commerce, etc.) from a destination of the information sources. This application server unit **242** may include Starfish Software to provide the address book, calendar and to-do lists, and to allow the user to organize information. The application server unit **242** processes the retrieved information and provides the information to the VRU server **234** and the voice browser **250**. The VRU server **234** can provide an audio announcement to the user based upon the information using TTS synthesizing or human recorded voice. The application server unit **242** can also send tasks or requests (e.g., transactional information) received from the user to the information sources (e.g., a request to place an order for a pizza). The application server unit **242** can further receive user inputs from the VRU

server **234** based upon a speech recognition output. The application server unit **242** is preferably a PC.

The voice markup language server **251** is preferably connected to the LAN **240**. The voice markup language server **251** can include a database,
5 scripts and markup language documents or pages. The voice markup language server **251** is preferably a PC, such as, for example, a Windows NT compatible PC. It will also be recognized that the voice markup language server **251** can be an Internet server (e.g., a Sun Microsystems server).

The messaging server **255** is preferably connected to the LAN **240**, the
10 paging network **211**, an e-mail system **213** and a short message system (SMS) **290**. The messaging server **255** routes pages between the LAN **240** and the paging network **211**. The messaging server **255** is preferably a PC, such as, for example, a Windows NT compatible PC. The messaging server **255** can also provide direct storage. It is contemplated that the messaging
15 server **255** can reside externally from the communication node **212**.

The voice browser **250** is preferably connected to the LAN **240**. The voice browser **250** preferably receives information from the markup language servers **209**, **251**, **253**, **257**, the database server unit **244** and the content providers **208**, **221**. In response to voice commands or DTMF signals, the
20 voice browser **250** generates a content request (e.g., an electronic address) to navigate to a destination of one or more of the information sources. The content request can use at least a portion of a Uniform Resource Locator, an Internet Protocol, a page request, or e-mail.

After the voice browser **250** is connected to an information source, the
25 voice browser **250** preferably uses a Transmission Control Protocol/Internet Protocol connection to pass requests to the information source. The information source responds to the requests, sending at least a portion of the requested information, represented in electronic form, to the voice browser **250**. The information can be stored in a database, and can include text
30 content, markup language document or pages, non-text content, dialogs, audio sample data, recognition grammars, etc. The voice browser **250** then parses and interprets the information, further described below. The voice browser **250** can be integrated into the communication devices **201**, **202**, **203**, **204**, **205**.

As shown in **FIG. 5**, the content provider **208** is connected to the application server unit **242** of the communication node **212**, and the content provider **221** is connected to the gateway server unit **246** of the communication node **212** via the Internet **220**. The content providers **208**,
5 **221** can store various content information, such as news, banking, commerce, weather, traffic conditions, etc. The content providers **208**, **221** can include a server to operate WWW pages or documents in the form of a markup language. The content providers **208**, **221** can also include a database, scripts and/or markup language documents or pages. The scripts can include
10 images, audio, grammars, computer programs, etc. The content providers **208**, **221** execute suitable server software to send requested information to the voice browser **250**.

The voice mail unit **274** is preferably connected to the telephone switch **203** and the LAN **240**. The voice mail unit **274** can store voice mail messages
15 from parties trying to send messages to the communication node **212**. When a user accesses the electronic network **206**, the voice mail unit **274** can notify the user of new and stored messages. The user can access the messages to play, delete, store and forward the messages. When the user accesses a message, the message can be read to the user or can be displayed as textual
20 information on a communication device (e.g., a pager, a SMS **290**, or a PDA, etc.). The user can also access and operate external messages or mail systems remote from the electronic network **206**.

The FAX server unit **272** is preferably connected to the telephone switch **230** and the LAN **240**. The FAX server unit **272** receives and stores
25 facsimile information sent via the electronic network **206** or the carrier network **216**. Users can access the facsimile information to play, store, delete, and forward the information. The facsimile information can be read via the TTS unit **252** or can be displayed as textual information on a suitable communication device. The FAX server unit **272** preferably comprises a PC,
30 such as, for example, a Windows NT compatible PC or a Dialogue Fax Server.

Further information regarding communication system **200** is disclosed in U.S. Patent Application No. **09/141,485**, entitled Telecommunication

System and Methods Therefore, filed August 27, 1998, the entire disclosure of which is incorporated herein.

- 5 It should be appreciated that the embodiments described above are to be considered in all respects only illustrative and not restrictive. The scope of the invention is indicated by the following claims rather than by the foregoing description. All changes that come within the meaning and range of equivalents are to be embraced within their scope.

1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2581
2582
2583
2584
2585
2586
2587
2588
2589
2590
2591
2592
2593
2594
2595
2596
2597
2598
2599
2600
2601
2602
2603
2604
2605
2606
2607
2608
2609
2610
2611
2612
2613
2614
2615
2616
2617
2618
2619
2620
2621
2622
2623
2624
2625
2626
2627
2628
2629
2630
2631
2632
2633
2634
2635
2636
2637
2638
2639
2640
2641
2642
2643
2644
2645
2646
2647
2648
2649
2650
2651
2652
2653
2654
2655
2656
2657
2658
2659
2660
2661
2662
2663
2664
2665
2666
2667
2668
2669
2670
2671
2672
2673
2674
2675
2676
2677
2678
2679
2680
2681
2682
2683
2684
2685
2686
2687
2688
2689
2690
2691
2692
2693
2694
2695
2696
2697
2698
2699
2700
2701
2702
2703
2704
2705
2706
2707
2708
2709
2710
2711
2712
2713
2714
2715
2716
2717
2718
2719
2720
2721
2722
2723
2724
2725
2726
2727
2728
2729
2730
2731
2732
2733
2734
2735
2736
2737
2738
2739
2740
2741
2742
2743
2744
2745
2746
2747
2748
2749
2750
2751
2752
2753
2754
2755
2756
2757
2758
2759
2760
2761
2762
2763
2764
2765
2766
2767
2768
2769
2770
2771
2772
2773
2774
2775
2776
2777
2778
2779
2780
2781
2782
2783
2784
2785
2786
2787
2788
2789
2790
2791
2792
2793
2794
2795
2796
2797
2798
2799
2800
2801
2802
2803
2804
2805
2806
2807
2808
2809
2810
2811
2812
2813
2814
2815
2816
2817
2818
2819
2820
2821
2822
2823
2824
2825
2826
2827
2828
2829
2830
2831
2832
2833
2834
2835
2836
2837
2838
2839
2840
2841
2842
2843
2844
2845
2846
2847
2848
2849
2850
2851
2852
2853
2854
2855
2856
2857
2858
2859
2860
2861
2862
2863
2864
2865
2866
2867
2868
2869
2870
2871
2872
2873
2874
2875
2876
2877
2878
2879
2880
2881
2882
2883
2884
2885
2886
2887
2888
2889
2890
2891
2892
2893
2894
2895
2896
2897
2898
2899
2900
2901
2902
2903
2904
2905
2906
2907
2908
2909
2910
2911
2912
2913
2914
2915
2916
2917
2918
2919
2920
2921
2922
2923
2924
2925
2926
2927
2928
2929
2930
2931
2932
2933
2934
2935
2936
2937
2938
2939
2940
2941
2942
2943
2944
2945
2946
2947
2948
2949
2950
2951
2952
2953
2954
2955
2956
2957
2958
2959
2960
2961
2962
2963
2964
2965
2966
2967
2968
2969
2970
2971
2972
2973
2974
2975
2976
2977
2978
2979
2980
2981
2982
2983
2984
2985
2986
2987
2988
2989
2990
2991
2992
2993
2994
2995
2996
2997
2998
2999
3000
3001
3002
3003
3004
3005
3006
3007
3008
3009
3010
3011
3012
3013
3014
3015
3016
3017
3018
3019
3020
3021
3022
3023
3024
3025
3026
3027
3